

## Important directions for collecting goods

**Our products must be transported in closed trucks with a rolling cover. Loading is carried out exclusively by crane from above. Exception: sandwich elements are loaded onto open trucks with a forklift truck.**

**The following vehicle requirements apply to trucks over 7.5 tons:**

- Perfectly operating rolling cover
- Undamaged bodies in perfect working order
- High end panel (min. 2100 mm) undamaged
- Minimum internal loading area width of 2460 mm
- All stanchions and slat boards present and undamaged
- Tailboard locking mechanisms in working order
- Tail lift locked and undamaged
- Adequate and suitable lashing points (min. 12)
- At least 12 lashing straps DIN 12195-2 (STF 240daN); hooks must fit the lashing points (missing straps must be procured on site)
- All lashing gear must be technically flawless and be checked regularly
- The truck floor must be dry and clean. There must not be any other products or packaging material on the floor (broom on board)
- There must be at least 20 slip-proof mats and 40 edge protectors provided on the truck.

The loading times from 7.30 a.m. to 11.30 a.m. from Monday to Friday must be adhered to

**Unsuitable vehicles will not be loaded for safety reasons – in this case, the journey to the plant/provision of vehicle will not be paid for!**

In the case of divergences from these requirements or the use of trucks under 7.5 tons, our transport planning department must be contacted beforehand in order to clarify the appropriate requirements.